CONSTRUCTION PRODUCTS REGULATIONS 2013

UKCA DECLARATION OF PERFORMANCE

This Declaration of Performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom, under the sole responsibility of the manufacturer identified below.

Identification code:	INS-RSD-05
Intended use:	Insulated Roller Shutter Door For External Use
Manufacturer:	Lotinga Industrial Doors®, Jezreels Barn, Rodmersham Court Farm, Church Street, Rodmersham, Sittingbourne, Kent ME9 0QA

Authorised representative: **Not Applicable** Assessment and verification of constancy of performance: **Systems 3 & 4**

Relevant harmonised standard: BS EN 13241:2003+A2:2016 Exova Warrington APT 0621 performed Initial Type Tests under System 3 and issued test report No's 144116, 305384, WIL 328309/A, WIL 328309/B, WIL 328309/C, WIL 328309/D

European Technical Assessment: **Not Applicable** Declared performance:

Essential Requirement	Declared perfor- mance	AVCP System	Harmonised standard	
Water Tightness	NPD	NPD		
Dangerous Substances	None	None		
Resistance to wind load	Class +5	3	1	
Thermal resistance	3" - 4.5 W/(m2.K) 4" - 4.3 W/(m2.K)	3		
Air permeability	NPD	NPD	EN 13241: 2003 + A2 : 2016	
Safe opening (for vertically moving doors)	Pass	3		
Definition of geometry of glass com- ponents	NPD	NPD		
Mechanical resistance and stability	Pass	4		
Operating forces (for power - operat- ed doors)	Pass	3		
Durability of water tightness, thermal resistance and air permeability against degradation	NPD	NPD		

Specific Technical Documentation:

The performance of the product identified above is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Trina Lotinga (Partner)

P /s

Sittingbourne 29 July 2022

CONSTRUCTION PRODUCTS REGULATION

DECLARATION OF PERFORMANCE

No. 0005 CPR 11-2019

Identification code:	Insulated Roller Shutter Door	
Serial number:		
Intended use:	External door for vehicle access	
Manufacturer:	Lotinga Industrial Doors®, Jezreels Barn, Rodmersham Court Farm, Church Street, Rodmersham, Sittingbourne, Kent ME9 0QA	

Authorised representative: Not Applicable

Assessment and verification of constancy of performance: Systems 3 & 4

Relevant harmonised standard: BS EN 13241:2003+A2:2016

Exova Warrington APT 0621 performed Initial Type Tests under System 3 and issued test report No's 144116, 305384, WIL 328309/A, WIL 328309/B, WIL 328309/C, WIL 328309/D

European Technical Assessment: **Not Applicable** Declared performance:

Essential Requirement	Declared perfor- mance	AVCP Sys- tem	Harmonised stand- ard
Water Tightness	NPD	NPD	
Dangerous Substances	None	None	
Resistance to wind load	Class +5	3	
Thermal resistance	3" - 4.5 W/(m2.K) 4" - 4.3 W/(m2.K)	3	
Air permeability	NPD	NPD	EN 13241: 2003 + A2 : 2016
Safe opening (for vertically moving doors)	Pass	3	A2 . 2010
Definition of geometry of glass compo- nents	NPD	NPD	
Mechanical resistance and stability	Pass	4	
Operating forces (for power - operated doors)	Pass	3	
Durability of water tightness, thermal re- sistance and air permeability against deg- radation	NPD	NPD	

Specific Technical Documentation:

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Trina Lotinga (Partner)

Phas

Sittingbourne 1 November 2019